



# Introducing Labelmoto®

## COMPARE THE NEW MODELS

ELECTRIC/AUTOMATIC LABEL DISPENSERS

Model #	LD6025	LD6050	LD6100	LDX6025	LDX6050	LDX6100
DESCRIPTION	<ul style="list-style-type: none"> <li>Replaces LD5000</li> <li>For short length and tiny barcode type labels</li> <li>Auto peel and advance</li> <li>Photosensor accuracy and reliability</li> <li>All metal construction</li> </ul>	<ul style="list-style-type: none"> <li>Replaces LD5100</li> <li>For most labels (barcodes, packaging, etc.)</li> <li>Auto peel and advance</li> <li>Photosensor accuracy and reliability</li> <li>All metal construction</li> </ul>	<ul style="list-style-type: none"> <li>New SuperSpeed machine! (2X Faster)</li> <li>For most labels (barcodes, packaging, etc.)</li> <li>Auto peel and advance</li> <li>Photosensor accuracy and reliability</li> <li>All metal construction</li> </ul>	<ul style="list-style-type: none"> <li>New machine!</li> <li>For wide, short length labels (long barcodes, etc.)</li> <li>Auto peel and advance</li> <li>Photosensor accuracy and reliability</li> <li>All metal construction</li> </ul>	<ul style="list-style-type: none"> <li>Replaces LD7000</li> <li>For wider packaging type labels</li> <li>Auto peel and advance</li> <li>Photosensor accuracy and reliability</li> <li>All metal construction</li> </ul>	<ul style="list-style-type: none"> <li>New SuperSpeed machine! (2X Faster)</li> <li>For wider packaging type labels</li> <li>Auto peel and advance</li> <li>Photosensor accuracy and reliability</li> <li>All metal construction</li> </ul>
MODEL REPLACED	LD5000	LD5100	N/A*	N/A*	LD7000	N/A*
LINER CAPACITY WIDTH	.25" to 4.5" (6 to 114mm)	.25" to 4.5" (6 to 114mm)	.25" to 4.5" (6 to 114mm)	.25" to 7" (6 to 178mm)	.25" to 7" (6 to 178mm)	.25" to 7" (6 to 178mm)
LABEL LENGTH	.125" to 6" (3 to 152mm)	.5" to 6" (13 to 152mm)	.5" to 6" (13 to 152mm)	.125" to 6" (3 to 152mm)	.5" to 6" (13 to 152mm)	.5" to 6" (13 to 152mm)
ROLL CAPACITY	12" (31cm)	12" (31cm)	12" (31cm)	12" (31cm)	12" (31cm)	12" (31cm)
FEED SPEED	1.6"/sec** (3.9cm/sec)	3.3"/sec** (8cm/sec)	6.6"/sec** (16cm/sec)	1.6"/sec** (3.9cm/sec)	3.3"/sec** (8cm/sec)	6.6"/sec** (16cm/sec)
BUILT-IN HANG DESIGN	YES	YES	YES	YES	YES	YES
DIMENSIONS	10.8" L x 13.2" W x 14.5" H 27.4cm x 33.5cm x 36.8cm	10.8" L x 13.2" W x 14.5" H 27.4cm x 33.5cm x 36.8cm	10.8" L x 13.2" W x 14.5" H 27.4cm x 33.5cm x 36.8cm	14.5" L x 15.5" W x 11" H 36.8cm x 39.4mm x 27.9mm	14.5" L x 15.5" W x 11" H 36.8cm x 39.4mm x 27.9mm	14.5" L x 15.5" W x 11" H 36.8cm x 39.4mm x 27.9mm
ELECTRICAL REQUIREMENTS	100/120V 50/60Hz, <1 amp 230V 50/60Hz C€ Available	100/120V 50/60Hz, <1 amp 230V 50/60Hz C€ Available	100/120V 50/60Hz, <1 amp 230V 50/60Hz C€ Available	100/120V 50/60Hz, <1 amp 230V 50/60Hz C€ Available	100/120V 50/60Hz, <1 amp 230V 50/60Hz C€ Available	100/120V 50/60Hz, <1 amp 230V 50/60Hz C€ Available
WEIGHT	10.5 lbs (4.76 kg)	10.5 lbs (4.76 kg)	10.5 lbs (4.76 kg)	11.3 lbs (5.12 kg)	11.3 lbs (5.12 kg)	11.3 lbs (5.12 kg)
DISPENSING CLEAR LABELS?	Order LD6025C	Order LD6050C	Order LD6100C	Order LDX6025C	Order LDX6050C	Order LDX6100C

\*This is a brand new model. \*\*Feed Speed calculated at 60Hz with a 1.25" (31.75mm) take up hub.

**START International**  
4270 Airborn Drive  
Addison, TX 75001  
+1 (972) 248-1999  
www.STARTinternational.com

PROUD MANUFACTURERS OF:

