

## Electric

### Additional info for LD6050

- Will dispense labels and die-cut parts
- Adjustable strip plate for hard-to-release labels
- Will accommodate core sizes of 1" (25 mm) and 3" (76mm)
- Automatically rewinds liner scrap for a cleaner working environment
- Liner scrap is easily removed
- No tools required for adjusting to different size labels
- No maintenance required

### Additional info for LD6025

- Will dispense labels and die-cut parts
- Adjustable strip plate for hard-to-release labels
- Will accommodate core sizes of 1" (25 mm) and 3" (76mm)
- Can dispense paper, polyester, vinyl, acetate, foam, foil, etc.
- Automatically rewinds liner scrap for a cleaner working environment
- Liner scrap is easily removed
- No tools required for adjusting to different size labels
- No maintenance required
- All 230V machines are CE Certified

### SPECIAL APPLICATIONS

- For clear labels and materials, please select Model # LD6050C or LD6025C

### Suggested accessory:

LDHANGER16

16" (40.6cm) wide

See Accessories Page 31



For 230V machines, please add "-2" to the end of the model number. (Example: LD6050-2)

## LD6050

### 4.75" (121mm) wide — Electric Label Dispenser "HIGH SPEED"

- Ideal for virtually any kind of label from bar code to packaging
- Automatically peels and advances labels
- Built-in 1/4" bracket for hanging capability for use with workbenches and LDHANGER16
- Photosensor accuracy and reliability
- Anodized aluminum construction
- High-torque motor for heavy rolls of labels
- Will dispense labels from .25" to 4.75" (6 to 121mm) in width
- Will dispense labels from .50" to 6" (13 to 152mm) in length
- Made in U.S.A.

#### COMMON MATERIALS



## LD6050FDA

### USDA/FDA Compliant Coating and CFIA Approved

- USDA/FDA compliant coating ideal for food and pharmaceutical industries



## LD6025


### 4.75" (121mm) wide — Electric Label Dispenser

- Ideal for short length and tiny bar code labels
- Automatically peels and advances labels
- Built-in 1/4" bracket for hanging capability for use with workbenches and LDHANGER16
- Photosensor accuracy and reliability
- Anodized aluminum construction
- High-torque motor for heavy rolls of labels
- Will dispense labels from .25" to 4.75" (6 to 121mm) in width
- Will dispense labels from .125" to 6" (3 to 152mm) in length
- Made in U.S.A.

#### COMMON MATERIALS




HANGING BRACKET



Patented



HANGING BRACKET



Patented



MODEL #	Liner Capacity	Width	Length	Roll Capacity	Feed Speed*	Dimensions	Electrical Requirements	Weight		
LD6025	.25" to 4.75"	(6mm to 121mm)	.125" to 6"	(3mm to 152mm)	12"	(31cm)	1.6"/sec* (3.9cm/sec.)	10.8"(L) x 10.8"(W) x 14.5"(H) 27.4cm(L) x 27.4cm(W) x 36.8cm(H)	100/115V AC, 0.75A 60Hz (220-240V AC, 0.4A 50Hz <b>CE</b> )	7.0 lbs (3.18 kg)
LD6050	.25" to 4.75"	(6mm to 121mm)	.50" to 6"	(13mm to 152mm)	12"	(31cm)	3.3"/sec* (8cm/sec.)	10.8"(L) x 10.8"(W) x 14.5"(H) 27.4cm(L) x 27.4cm(W) x 36.8cm(H)	100/115V AC, 2.5A 60Hz (220-240V AC, 1.8A 50/60Hz <b>CE</b> )	8.8 lbs (3.97 kg)
LD6100	.25" to 4.75"	(6mm to 121mm)	.50" to 6"	(13mm to 152mm)	12"	(31cm)	6.6"/sec* (16.8cm/sec.)	10.8"(L) x 10.8"(W) x 14.5"(H) 27.4cm(L) x 27.4cm(W) x 36.8cm(H)	100/115V AC, 2.5A 60Hz (220-240V AC, 2A 50Hz <b>CE</b> )	8.8 lbs (3.97 kg)

\*Feed Speed calculated at take-up hub origin. Feed Speed will increase as material dispenses. Speed calculated at 60Hz.