


## Specialty & Hand-Held

Additional info for LR4500 and LR4500W

- Accepts 1.25 and 3" (32mm and 76 mm) roll core sizes
- Operates on 12V DC with an included 100/120V AC adapter
- Made in the U.S.A. 



### LR4500

#### Label Rewinder

- Rewinds labels from thermal transfer printers or reels
- 2 speeds (slow and fast)
- Bi-directional (forward and backward)
- Maximum material width 4.5" (114mm)
- Maximum outside diameter of roll 9" (251mm)



### LR4500W

#### Wide Label Rewinder

- Rewinds labels from thermal transfer printers or reels
- 2 speeds (slow and fast)
- Bi-directional (forward and backward)
- Maximum material width 7.0" (178mm)
- Maximum outside diameter of roll 9" (251mm)
- Use 2 LR4500Ws to unwind and rewind labels for proper orientation of labels

MODEL #	Liner Capacity Width	Length	Roll Capacity	Feed Speed*	Core	Dimensions	Electrical Requirements	Weight
LR4500	.25" to 4.5" (6mm to 114mm)	Variable	9" (251mm)	Slow/Fast	1.25" & 3"	11" (L) x 6" (W) x 10.4" (H) 27.9cm (L) x 15.2cm (W) x 26.4cm (H)	12V DC with Universal transformer, 100V - 240V <b>CE</b>	8.5 lbs (3.6 kg)
LR4500W	.25" to 7" (6mm to 178mm)	Variable	9" (251mm)	Slow/Fast	1.25" & 3"	12.75" (L) x 6" (W) x 10.4" (H) 32.4cm (L) x 15.2cm (W) x 26.4cm (H)	12V DC with Universal transformer, 100V - 240V <b>CE</b>	8.7 lbs (3.9 kg)