Carousel / Wrapper

T D A 0 2 5 B

Electric Carousel Tape Dispenser

- Ideal for multi-operator applications
- Automatically feeds and cuts tape to a definite length
- Unique feed system places tape on carousel for easy removal
- Accepts tape widths from .12" to .98" (3 to 25mm)
- Cuts lengths from .6" to 2.76" (15 to 70mm)

Features

PHOTOSENSOR ACTUATION ONE-TOUCH ROTATION





T D W 0 1 9

Manual Tape Wrapper

- Efficiently wraps tape around wires, harnesses, bundles, tubing, etc.
- Accepts tape widths from .375" .75" (9 19mm)
- Maximum bundle diameter of 2" (51mm)
- Heavy-duty solid aluminum frame construction







TAPE Dispensers

Electric

Additional info for TDA025B

- Allows up to 20 pieces of tape to be cut at the touch of a button
- Accepts many different core diameter tapes
- Safety switch on cover
- Small footprint
- Photosensor
- Three cut modes: automatic, semi-automatic and manual
- 5.9" (150mm) maximum outside diameter roll
- Light weight
- All 230V machines are **C** Certified

Additional info for TDW019

- Simple, compact, and easy to use
- Holes in base to mount to workbench
- Uses any brand of tape
- Maintenance-free design
- Safety blade guard
- 7" (178mm) maximum outside roll diameter
- 1.25" (32mm) tape core provided
- Optional tape cores:
 - -1.50" (38mm): Part # TDW019-04B -3" (76mm): Part # TDW019-04C
- Made in the U.S.A.

For 230V machines, please add "-2" to the end of the model number. (Example: TDA025B)

| MODEL # | Tape Width | Cut Length | Max. Outside Dia. of Roll | Core Diameter | Accuracy of Cut* | Tape Cutter | Feed Type | Adjustable Tape Spacing | Length Setting | Weight |
|---------|-----------------------------|------------------------------|------------------------------|------------------|---------------------|----------------|--------------|----------------------------|-------------------|---------------------|
| TDA025B | .12" to .98" (3 to 25mm) | .6" to 2.76" (15 to 70mm) | 5.9″ (150mm) | universal | .08″ (2mm) | automatic | carousel | yes | manual | 4.2 lbs (1.9 kg) |

Dimensions: 10.2"(L) x 5"(W) x 5.9"(H) 25.9cm(L) x 12.7cm(W) x 15cm(H) Electrical requirements: 117V 50/60Hz, <1 amp (230V 50/60Hz CC) *Dependent on material

| | Tape Width Dia. of Roll | | Max. Outside Diameter | Core Diameter | Dimensions | Max. Bundle | | |
|--------|-------------------------|---------------------------|--------------------------|------------------|----------------|---|--|--|
| TDW019 | 2" (51mm) | .375" to .75" (9 to 19mm) | 7" (178mm) | 1.25" (32mm) | 5 lbs (2.27kg) | 10.5"(L) x 6"(W) x 11.25"(H) 267mm(L) x 152mm(W) x 287mm(H) | | |

