

Heavy-Duty Wide Tape Dispensers

Additional info for TDA150

- Heavy-duty metal construction
- All-metal gears and advancement rollers
- 4 modes of operation: manual feed-manual cut, manual feed and cut, auto feed and cut, and interval feed and cut
- Guillotined cut for a straight edge piece of tape
- Digital push-switch display for easy length adjustments
- Safety interlock
- Accuracy +/- .04" (1mm) (dependent on type of tape)
- 9" (251mm) maximum outside diameter roll
- Comes with 3" (76mm) diameter core
- For Super-Speed Dispensing of Tapes (13.2" per second) order Model # TDA150-FM
- All 230V machines are **CE** Certified
- Engineered in USA



TDA150

Electric "Heavy-Duty" Tape Dispenser – 150mm Wide

- Ideal for high production of repetitive taping for industrial applications
- Program a defined length and automatically advance and cut tape
- Accepts tape widths from .25" to 5.9" (6 to 150mm)
- Cuts lengths from 1.6" to 394" (40 to 9999mm)

Suggested accessory:
TDSTAND03
Max. OD 20" (508mm)
See Accessories Page 31



TDA150-NS

- Modified TDA150 with special tape advancement rollers **for foam and high tack tapes**
- Maximum material thickness: .125" (3mm) foam, .0625" (1.5mm) VHB®. Materials beyond the specification must be tested; See Material Evaluation form on Page 32



TDA150-NM

- Modified TDA150 with special non-marking advancement rollers **for protective films and foil tapes**
- Ideal for high production of repetitive taping for industrial applications

For 230V machines, please add "-2" to the end of the model number. (Example: TDA150-2)

MODEL #	Tape Width	Cut Length	Max. Outside Dia. of Roll	Core Diameter	Accuracy of Cut*	Feed Speed*	Weight	Dimensions
TDA150	.25" to 5.9" (6 to 150mm)	1.6" to 394" (40 to 9999mm)	9" (220mm)	3" (76mm)	+/- .040" (+/- 1mm)	6.6"/sec (16.8cm/sec)	37 lbs (16.8 kg)	10.25" (L) x 13" (W) x 14" (H) 26.0cm (L) x 33.0cm (W) x 35.6cm (H)
TDA150-FM	.25" to 5.9" (6 to 150mm)	1.6" to 394" (40 to 9999mm)	9" (220mm)	3" (76mm)	+/- .040" (+/- 1mm)	13.2"/sec (33.5cm/sec)	37 lbs (16.8 kg)	10.25" (L) x 13" (W) x 14" (H) 26.0cm (L) x 33.0cm (W) x 35.6cm (H)

Electrical requirements: 115V 50/60Hz <2 amps (230V 50/60Hz **CE**) *Dependent on material.