

Electric

zcM2000

Electric Tape Dispenser with Multiple Programmable Tape Lengths

- Program 3 defined lengths and automatically advance and cut tape; zcM2000X features 10 defined lengths
- Two operating modes: on-demand lengths or consecutive
- Accepts tape widths from .28" to 2" (7 to 51mm)
- Cuts tape lengths from .79" to 39" (20 to 999mm)



Example: 30, 45, 60mm

zcM2200

Electric Tape Dispenser with Safety Guard Cutting Head and 3 Programmable Tape Lengths

- Safety guard system prevents activation of cutter when foreign objects are present (fingers, tools, etc.)
- Program 3 defined lengths and automatically advance and cut tape
- Ideal for medium to high production of repetitive taping for industrial applications
- Two operating modes: on-demand lengths or consecutive
- Accepts tape widths from .28" to 2" (7 to 51mm)
- Cuts tape lengths from 1.2" to 39" (30 to 999mm)



Accessory Options

See page 30 or visit <http://STARTinternational.com/en/products/accessories>

For 230V machines, please add "-2" to the end of the model number. (Example: zcM2200-2)

MODEL #	Tape Width	Programmable Memory	Cut Length	Max. Outside Dia. of Roll	3-in-1 Core Holder	Accuracy of Cut*	Length Setting	Weight	Dimensions
zcM2000	.28" to 2.0" (7 to 51mm)	3	.79" to 39" (20 to 999mm)	7" (178mm)	1", 1.4" 3" (25, 35, 76mm)	+/- .04" (1mm)	digital (LED)	5.6 lbs (2.54 kg)	9.7"(L) x 5.3"(W) x 6.3"(H) 24.5cm(L) x 13.5cm(W) x 16cm(H)
zcM2200	.28" to 2.0" (7 to 51mm)	3	1.2" to 39" (30 to 999mm)	7" (178mm)	1", 1.4" 3" (25, 35, 76mm)	+/- .04" (1mm)	digital (LED)	6 lbs (2.72 kg)	9.8"(L) x 5.3"(W) x 6.5"(H) 25cm(L) x 13.5cm(W) x 16.5cm(H)

Electrical requirements: 117V 50/60Hz, <1 amp (230V 50/60Hz **CE**) *Dependent on material