


**Electric**

# Unparalleled Performance For 30 Years

**Additional info for zcM1000**

- Photocell actuated feed & cut or push-button feed & cut
- Guillotined cut for a straight edge piece of tape
- LED Digital length adjustment
- Manual override of preset lengths
- Blades good for up to 200,000 cuts (dependent on type of material)
- Steel frame for durability
- Cabinet made from flame retardant antistatic composite (auto ignition of 896°F/480°C)
- Comes with a 3-in-1 core (1" (25mm), 1.4" (35mm), 3" (76mm))
- Adjustable pressure roller for various thicknesses of tape
- Accuracy of tape length is +/- .04" (1mm) (dependent on type of material)
- Many available accessories fit this machine. See Accessories section.
- All 230V machines are CE Certified
- Made in Japan



**Accessory Options**

See page 30 or visit <http://STARTinternational.com/en/products/accessories>

Visit [www.youtube.com/user/startintl](http://www.youtube.com/user/startintl) to see our dispensers in action.

For 230V machines, please add "-2" to the end of the model number. (Example: zcM1000-2)



**zcM1000**

**Electric Tape Dispenser**

- Ideal for medium to high production of repetitive taping for industrial applications
- Program a defined length and automatically advance and cut tape
- Accepts tape widths from .28" to 2" (7 to 51mm)
- Cuts tape lengths from .79" to 39" (20 to 999mm)

**Features**

**3-IN-1 CORE HOLDER**



**EASY TO OPERATE**



**Applications**



**zcM1000E**

**For Dispensing Two Rolls of Tape**

- Cutting head with dual photo sensors/dual core for dispensing two rolls of tape
- Accepts tape widths from .28" to 2" (7 to 51mm)
- Cuts tape lengths from .79" to 39" (20 to 999mm)

MODEL #	Tape Width	Cut Length	Max. Outside Dia. of Roll	3-in-1 Core Holder	Accuracy of Cut*	Feed Speed*	Length Setting	Weight	Dimensions
zcM1000	.28" to 2.0" (7 to 51mm)	.79" to 39" (20 to 999mm)	7" (178mm)	1", 1.4", 3" (25, 35, 76mm)	+/- .04" (1mm)	5.7"/sec 14.5 cm/sec	Digital (LED)	5.6 lbs (2.54 kg)	9.7"(L) x 5.3"(W) x 6.3"(H) 24.5cm(L) x 13.5cm(W) x 16cm(H)

Electrical requirements: 117V 50/60Hz, <1 amp (230V 50/60Hz CE) \*Dependent on material